


DELPHION

No active trail

[Select CR](#)[Stop Tracking](#)[RESEARCH](#)[Log Out](#) [Work Files](#) [Saved Searches](#)[My Account](#)Search: [Quick/Number](#) [Boolean](#) [Advanced](#) [Derwent](#)[Help](#)

The Delphion Integrated View

Get Now: ☒ PDF | [More choices...](#)Tools: [Add to Work File](#) [Create new Work File](#)[Add](#)View: INPADOC | [Jump to: Top](#)[Email this to a friend](#)Title: **JP62251949A2: ERROR CORRECTING METHOD FOR MEMORY DEVICE**Country: **JP Japan**Kind: **A**Inventor: **OGASAWARA KOICHI;**Assignee: **MITSUBISHI ELECTRIC CORP**[News, Profiles, Stocks and More about this company](#)Published / Filed: **1987-11-02 / 1986-04-25**Application Number: **JP1986000096332**IPC Code: **G06F 12/16;**Priority Number: **1986-04-25 JP1986000096332**[View Image](#)**1 page**

Abstract: **PURPOSE:** To facilitate finding troubles of an error detecting circuit and a correcting circuit by checking again data after error correction to improve the reliability of a memory device.

CONSTITUTION: When an uncorrectable error is decided a detecting circuit 4 outputs the position of the error bit to an analyzing circuit 7 as a syndrome. The circuit 7 decides whether the error bit is within data or a check code, and the contents of a read data latch 2 are directly written in a read data buffer 6 if data bits have not the error. If data bits have the error, the bit indicated by the syndrome in data is corrected, and this corrected data is checked again by the contents of a check code latch 3. If there are no errors as the result of recheck, the processing is normally terminated; but other-wise, the processing is abnormally terminated.

COPYRIGHT: (C)1987,JPO&Japio

INPADOC
Legal Status:


None

[Get Now: Family Legal Status Report](#)

Family:

[Show 2 known family members](#)Other Abstract
Info:

None

[Nominate this for the Gallery...](#)**THOMSON**

Copyright © 1997-2005 The Thomson Corporation

BEST AVAILABLE COPY